


NPWD-C1.TC NPWD-C11.TC

Single input, single output

Single input, dual output

Input: TC
Output: 4 ~ 20 mA

This temperature transmitter converts the thermocouple signals to current signals. It needs an independent power supply. The input, output, and power supply are galvanically isolated from each other. Modify parameters by using PC or a handheld programmer.




Parameters

Power supply:	85 V AC ~ 265 V AC (90 V DC ~ 360 V DC)
Power dissipation:	0.8 W (220V AC, single output full-load) 2.5 W (220V AC, double output full-load)
Input signal:	K, E, S, B, J, T, R, N, etc
Line resistance:	20 per line (RTD)
Output signal:	4 ~ 20mA (sink/source)
Load resistance:	source: $R_L \leq 550$ sink: $R_L < [(U-3)/0.02]$; U: Loop power supply
Compensation accuracy:	1 °C (Temperature compensation range: -20 °C ~ +60 °C)
Temperature drift:	30 ppm/°C
Response time:	500 ms
Electromagnetic compatibility:	IEC 61326-3-1
Dielectric strength:	1500 V AC (Input/Output/Power supply)
Insulation resistance:	100 M (Input/Output/Power supply)
Operation temperature:	-20 °C ~ +60 °C
Storage temperature:	-40 °C ~ +80 °C
Dimension:	17.8 mm (W) × 110 mm (H) × 117 mm (D)
Output states:	Whatever input fault status (except breakage), the output follows the input within measuring range. And the maximum value would not exceed the 110% of the upper limit of the measuring range (e.g. When the output signal type is 0 ~ 20 mA, the minimum output value may be 0 mA, the maximum output value would not exceed 22 mA)

Range and Conversion accuracy list

Type	Range	Min.span/Accuracy	
K	-200°C ~ +1372°C	< 300°C, ±0.3°C	300°C, ±0.1% F.S.
E	-100°C ~ +1000°C	< 300°C, ±0.3°C	300°C, ±0.1% F.S.
J	-100°C ~ +1200°C	< 300°C, ±0.3°C	300°C, ±0.1% F.S.
N	-200°C ~ +1300°C	< 300°C, ±0.3°C	300°C, ±0.1% F.S.
S	-50°C ~ +1768°C	< 500°C, ±0.5°C	500°C, ±0.1% F.S.
R	-50°C ~ +1768°C	< 500°C, ±0.5°C	500°C, ±0.1% F.S.
T	-20°C ~ +400°C	< 300°C, ±0.3°C	300°C, ±0.1% F.S.
B	+400°C ~ +1820°C	< 500°C, ±0.5°C	500°C, ±0.1% F.S.

Wiring diagram



Model rules

NPWD-C \square \square .TC

The second output signal^{note1}
Default: null
The first output signal^{note1}

note1 output signal

Number	Output signal
1	4 ~ 20 mA
2	1 ~ 5 V
3	0 ~ 10 mA
4	0 ~ 5 V
5	0 ~ 10 V
6	0 ~ 20 mA