

NPFSR-K4F31AMD

3NO+1NC



24V AC/DC
0.85 ~ 1.1
50Hz ~ 60Hz
2.2W/24V DC, 5.4VA/24V AC
50mA/24V DC
15
3NO+1NC
AgSnO ₂ +0.2μmAu
AC-15: 5A/230V, DC-13: 5A/24V
10A gL/gG(NO), 6A gL/gG(NC)
100ms
: 30ms, : 100ms
: 30ms, : 100ms
20ms
IEC/EN 60947, IEC 61326-3-1, IEC/EN 61000-6-2, IEC/EN 61000-6-4
250V AC
6000V(1.2/50us)
1500V AC, 1 min
IEC 60947-1
10Hz ~ 55Hz, 0.35mm
III
2
IP20
-20°C ~ +60°C
-40°C ~ +80°C
2000 m
10×10 ⁶ cycles

PLd, ISO 13849
Cat.3, ISO 13849
20, ISO 13849
99%, ISO 13849
162, ISO 13849
68, ISO 13849
SIL2, IEC 61508
SIL CL2, IEC 62061
1, IEC 62061
99%, IEC 62061
1.65×10 ⁻⁵ /PTI=20年, IEC 61508
1.91×10 ⁻¹⁰ 1/h, IEC 62061
0, IEC 60204